



Manufacture Siemens 3 SB 22 mm

Pos.	Command devices		Weight gramm	Part No.	Type	Price EURO
1	Push button	1 NO + 1 NC	40		D	
2	Selector switch 0-1	2 positions 1 NO + 1 NC	50		W	
3	Selector switch 1-0-2	3 positions 2 NO + 2 NC	60		W	
4						
5						
6	Key switch 0-1	2 positions 1 NO + 1 NC	130		S	
7	Key switch 1-0-2	3 positions 2 NO + 2 NC	140		S	
8						
9						
10	Mushroom key switch latching	1 NO + 1 NC	80		PS	
11	Mushroom head push button latching	1 NC	60		PV	
12						
13						
14						
15	Contact block additional (max. 3 pcs.)	1 NO + 1 NC	10			
	Command and indicating devices					
16	Illuminated push button lamp 24 V AC	1 NO + 1 NC	40		LD	
17	Illuminated push button lamp 110 V operating voltage 220 V AC	1 NO + 1 NC	40		LD	
18	Illuminated push button lamp 24 V with transformer 220/24 V AC	1 NO + 1 NC	50		LD	
19						
20	Contact block additional (max. 3 pcs.)	1 NO + 1 NC	10			
	Indicating devices					
21	Indicator light lamp 24 V AC		40		L	
22	Indicator light lamp 110 V operating voltage 220 V AC		40		L	
23	Indicator light lamp 24 V with transformer 220/24 V AC		50		L	
24						
25						
	Special devices					
26	Drilling diameter 22 mm					
27	Blind plug 22					
28						
29						
30	Push button with 2 steps RTTG22KLK../MHR3/MT97/MTO	2 NO + 1 NC	200			
31	Push button with 2 steps XB 2 - BA 243	2 NO + 1 NC	250			
32						
33						
34						
35						
36						
37						
38						
39						
40						



Manufacture Siemens 3 SB 30 mm

Pos.	Command devices		Weight gramm	Part No.	Type	Price EURO
1	Push button	1 NO + 1 NC	50		D	
2	Selector switch 0-1 2 positions	1 NO + 1 NC	60		W	
3	Selector switch 1-0-2 3 positions	2 NO + 2 NC	70		W	
4						
5						
6	Key switch 0-1 2 positions	1 NO + 1 NC	140		S	
7	Key switch 1-0-2 3 positions	2 NO + 2 NC	150		S	
8						
9						
10	Mushroom key switch latching	1 NO + 1 NC	90		PS	
11	Mushroom head push button latching	1 NC	70		PV	
12						
13						
14						
15	Contact block additional (max. 3 pcs.)	1 NO + 1 NC	10			
	Command and indicating devices					
16	Illuminated push button lamp 24 V AC	1 NO + 1 NC	50		LD	
17	Illuminated push button lamp 110 V operating voltage 220 V AC	1 NO + 1 NC	50		LD	
18	Illuminated push button lamp 24 V with transformer 220/24 V AC	1 NO + 1 NC	60		LD	
19						
20	Contact block additional (max. 2 pcs.)	1 NO + 1 NC	10			
	Indicating devices					
21	Indicator light lamp 24 V AC		50		L	
22	Indicator light lamp 110 V operating voltage 220 V AC		50		L	
23	Indicator light lamp 24 V with transformer 220/24 V AC		60		L	
24						
25						
	Special devices					
26	Drilling diameter 30 mm					
27	Blind plug 30					
28						
29	Push button with 2 steps SES 2	2 NO + 1 NC	300			
30	Push button with 2 steps ST 1-3-2	2 NO + 1 NC	300			
31	Push button with 3 steps ST 1-4-3	3 NO + 1 NC	350			
32	Push button with 4 steps ST 1-5-4	4 NO + 1 NC	400			
33	Push button with potentiometer PT 1-2-P	1 NO + 1 NC	350			
34	Wire-wound potentiometer T 237 linear Life 10 ⁶ switching cycles					
35	resistance 0,5/1,0/2,0/5,0 kOhm 1 Watt wiper current max. 10 mA					
36	Drive for potentiometer KEQ/418 with friction brake (potentiometer look 1/240)		250			
37	Summer EKS 24 V DC / 48 V AC / 220 V AC		250			
38	Knee button FAK-S/KC/I	1 NO + 1 NC	350			
39	Foot button 3SE 3902-OAB20	1 NO + 1 NC	450			
40						