



Pos.	Dimension outside in mm	Dimension inside in mm	Remarks	Weight kg	Part No.	Type	Price EURO
Steel sheet housing material thickness 1/1,5 mm Protection IP 54 painting RAL 7032 pebble-grey textured varnish							
1	200 x 200 x 92	166 x 166 x 90		1,3		B 200	
2	230 x 230 x 105	196 x 196 x 102		1,4		B 230	
3	230 x 340 x 105	196 x 306 x 102		1,5		B 230 x 340	
4	230 x 440 x 105	196 x 406 x 102		1,6		B 230 x 440	
5	250 x 250 x 150	216 x 216 x 147		1,6		B 250 x 250	
6							
7	150 x 400 x 105	116 x 366 x 102		3,2		B 150 x 400	
8	150 x 500 x 105	116 x 466 x 102		3,5		B 150 x 500	
9	150 x 600 x 105	116 x 566 x 102		3,8		B 150 x 600	
10	260 x 500 x 105	226 x 466 x 102		3,8		B 260 x 500	
11	260 x 600 x 105	226 x 566 x 102		4,2		B 260 x 600	
12	Dimensions special		on enquiry				
Plastic housing polycarbonat Protection IP 65 colour RAL 7035 fair-grey							
13	120 x 122 x 105	113 x 115 x 98		0,35		I 120 x 122	
14	120 x 160 x 140	113 x 134 x 133		0,6		I 120 x 160	
15	160 x 240 x 120	153 x 215 x 114		0,8		I 160 x 240	
16	160 x 360 x 100	153 x 352 x 94		1,0		I 160 x 360	
17	230 x 300 x 110	223 x 293 x 103		1,15		I 230 x 300	
18							
19							
20							
21							
22							
Plastic housing polyester Protection IP 65 colour RAL 7000 grey							
23	220 x 335 x 115	200 x 292 x 108	colour alternative RAL 9011 black	1,65		I 220 x 335	
24	220 x 465 x 115	200 x 432 x 108	colour alternative RAL 9011 black	2,24		I 220 x 465	
25	250 x 255 x 120	236 x 243 x 110		2,65		I 250 x 255	
26	250 x 400 x 120	236 x 386 x 110		3,65		I 250 x 400	
27	250 x 600 x 120	236 x 586 x 110		5,24		I 250 x 600	
28							
29							
30							
31							
32							
Accessory parts							
33	Hinges each housing (2 pcs.)			0,2			
34	Armrest with clamp adjustable straps			0,5			
35	Chest panel and straps			0,6			
36	Base bracket each housing (2 pcs.)			0,3			
37	Filter plug M 20		for air-condition	0,15			
38	Cable entry M 20 cable 7–13 mm		with anti-kink protection and strain relief	0,15			
39	Cable entry M 32 cable 11–21 mm		with anti-kink protection and strain relief	0,2			
40	Cable entry M 40 cable 19–28 mm		with anti-kink protection and strain relief	0,25			
41	Pillar with flange 100 x 100 x 535 mm high		flange 150 x 150 mm	14,0			
42	Indicating labels not engraved						
43	Engraved each 10 characters						
44							
45							